

Ultra Series

SPECIFICATIONS

1500SJ

Ultra Series Telescopic Boom Lifts

Reach Specifications

| | | |
|----------------------------------|-----------------------------------|--------------------|
| Platform Height | 150 ft (45.7 m) | |
| Horizontal Reach | 80 ft (24.38 m) | |
| Up and Over Height | — | |
| Swing | 360° Continuous | |
| Platform Capacity — Restricted | 1,000 lb (454 kg) | |
| Platform Capacity — Unrestricted | 500 lb (227 kg) | |
| Platform Rotator | 180° | |
| Jib | Length | |
| | 15 ft 2 in.–25 ft (4.62 m–7.62 m) | |
| | Horizontal Motion ¹ | For Transport Only |
| | Vertical Motion | 120° (+75°/-45°) |

Dimensional Data

| | | |
|---------------------|-----------------------------|-----------------------|
| A. Platform Size | 36 x 96 in. (0.91 x 2.44 m) | |
| B. Overall Width | Axles Retracted | 8 ft 2 in. (2.49 m) |
| | Axles Extended | 12 ft 6 in. (3.81 m) |
| C. Tailswing | | 5 ft 6 in. (1.67 m) |
| D. Stowed Height | | 10 ft (3.05 m) |
| E. Overall Length | Jib Stowed | 43 ft (11.45 m) |
| | Jib Deployed | 61 ft 9 in. (18.82 m) |
| F. Wheel Base | | 12 ft 6 in. (3.81 m) |
| G. Ground Clearance | Axle | 12 in. (30 cm) |
| | Chassis | 25.5 in. (65 cm) |
| Weight ² | | 48,000 lb (21,773 kg) |

Chassis

| | | |
|-------------------------------|------------------------------------|------------------------|
| Max Ground Bearing Pressure* | 113 psi (7.94 kg/cm ²) | |
| Drive Speed | 3.0 mph (4.8 km/h) | |
| Gradeability | 40% | |
| Turning Radius (Inside) | Axles Retracted | 14 ft 5 in. (4.39 m) |
| | Axles Extended | 8 ft (2.44 m) |
| Turning Radius (Outside) | Axles Retracted | 22 ft 6 in. (6.86 m) |
| | Axles Extended | 19 ft 4 in. (5.89 m) |
| Crab Steer Ratio ³ | | 1:1 |
| Axle Oscillation | | 12 in. (30 cm) |
| Tires/Type | | 445/50D710 Foam Filled |

Power Source


| | | |
|---------------------|-----------------------------|-------------------|
| Diesel Engine | Deutz TCD2.9L4 Tier 4 Final | 74.2 hp (55.4 kW) |
| Fuel Tank Capacity | | 31 gal (117 L) |
| Hydraulic Reservoir | | 55 gal (208 L) |
| Auxiliary Power | | 12V DC |
| Generator | | 7,500 Watt |

*Ground bearing pressure applies to standard tires.

1. Capacity is limited to 500 lb (227 kg) when Jib is extended.

2. Certain options or country standards increase weight.

3. Ratio of forward travel to lateral travel.



Standard Features

| |
|--|
| Platform: 36 x 96 in. |
| (0.91 x 2.44 m) Side Entry |
| 8 ft (2.44 m) JibPLUS® Boom |
| Selectable Capacity Envelope |
| 180° Hydraulic Platform Rotator |
| AC Receptacle in the Platform |
| 5 Degree Tilt Alarm/Indicator Light |
| All Motion Alarm |
| Swing-Out Engine Tray |
| 12V DC Auxiliary Power |
| Hourmeter |
| Control ADE® System |
| Full-time 4WD |
| 3 Selectable Steering Modes |
| Drive-out Extendible Axles |
| Oscillating Axle |
| Proportional Controls |
| Gull-Wing Hoods |
| 445/50D710 Foam Filled Rim Protector Lug Tread Tires |
| Platform Console Machine Status Light Panel* |
| Lifting/Tie Down Lugs |
| Engine Distress Warning/Shutdown — Selectable via JLG Analyzer |
| SkyGuard SkyLine™ |

Fall-Arrest Platform: 36 x 96 in.
(0.91 x 2.44 m) Side Entry

Self-Closing Gate

Light Package¹

Flashing Beacon

Soft-Touch System Platform
6 ft/8 ft (1.83 m/2.44 m)

ClearSky (US and Canada only)

Cold Weather Start²

Hostile Environment Kit³

Mesh to Top Rail

Operator Tool Tray

1. Includes platform mounted work lights and drive/backup lights.

2. Includes glow plugs, battery heater and oil tank heater.

3. Includes console cover, boom wipers and cylinder bellows.

Accessory Packages

| |
|------------------------------|
| SkyPower® Package |
| 7500 Watt Generator |
| • 240/120V Single Phase |
| • 240V 3 Phase |
| 1/2 in. Air Line to Platform |
| SkyWelder® |
| SkyCutter® |
| SkyGlazier® |
| Pipe Racks |

Available Options

Platform: 36 x 72 in.
(0.91 x 1.83 m) Side Entry

* Provides indicator lights at platform control console for system distress, fuel level, low fuel, 5 degree tilt light and foot switch status.

